MULTI-CLASS

TKO NOZZLE







Our Turbo Knockdown and Overhaul Nozzles (TKO Nozzles) are designed with a reservoir to house Encapsulator Agent concentrate for rapid deployment, resulting in instant knockdown while reducing heat and rendering fuel nonflammable. (NFPA 18A Section 7.7) This is perfect for combating today's vehicle fires.

FLOW RATE 75 LPM / 20 GPM

CAPACITY

≈ 0.5 GAL

PROPORTION

0% / 0.5% / 1% / 3%

STREAM

26 FT AT 100 PSI

FOG PATTERN

13 FT AT 100 PSI

COUPLING

1.5" NH-NST FITTING

PROTECTION

0% - 3%

NOZZLE UTILIZATION

In the event of an emergency, every second is precious. With the TKO Nozzle, there's no need to batch mix agent in your pumper or set up an eductor. When more concentrate is needed, simply unscrew the bottle and replace it in seconds. You'll gain the power to safely extinguish Class A, B, D and Lithium-ion Battery Fires at a moment's notice.

After extinguishment and overhaul is complete, you'll find there is **No Concentrate Waste** within 200 ft. of hose as Encapsulator Agent solution is generated at the nozzle, not the eductor. This gives you the option to alter your proportioning at the nozzle.

NFPA 18A ANX 4.3

Third-party Encapsulator Agent Testing



THE TKO NOZZLE IS IDEAL FOR FIREFIGHTING IN CONFINED SPACES

FLOW TIME

0.5%	320 SEC
1%	160 SEC
3%	60 SEC

POSTRATIO